



**Microsemi Corp.**  
The diode experts

SCOTTSDALE, AZ  
For more information call:  
(602) 941-6300

# 30S SERIES

## DESCRIPTION/FEATURES

- ECONOMICAL SERIES
- HIGH SURGE, 150 AMP MAXIMUM
- UNIVERSAL REPLACEMENT FOR MANY GLASS, EPOXY, ENCAPSULATED, AND METALLIC RECTIFIERS
- PEAK REVERSE VOLTAGES THROUGH 1000 VOLTS

## VOLTAGE RATINGS

Part Number	V <sub>WM</sub> - Working Peak Reverse Voltage (V) T <sub>J</sub> = -65°C to 175°C	V <sub>R</sub> - Max. Direct Reverse Voltage (V) T <sub>J</sub> = -65°C to 175°C
30S1	100	100
30S2	200	200
30S3	300	300
30S4	400	400
30S5	500	500
30S6	600	600
30S8	800	800
30S10	1000	1000

## ELECTRICAL SPECIFICATIONS


Symbol	Max. Value	Units	Conditions
I <sub>F(AV)</sub>	3.0	A	1 phase operation, 180° conduction. T <sub>L</sub> = 125°C, lead length 9.5 mm (0.375 in.)
I <sub>FSM</sub>	143	A	Half cycle 50 Hz sine wave or 6 ms rectangular pulse
	150		Half cycle 60 Hz sine wave or 5 ms rectangular pulse
	170		Half cycle 50 Hz sine wave or 6 ms rectangular pulse
	178		Half cycle 60 Hz sine wave or 5 ms rectangular pulse
I <sup>2</sup> <sub>t</sub>	103	A <sup>2</sup> s	t = 10 ms With rated V <sub>RRM</sub> applied following surge, initial T <sub>J</sub> = 175°C.
	94		t = 8.3 ms
	146		t = 10 ms With V <sub>RRM</sub> = 0 following surge, initial T <sub>J</sub> = 175°C.
	133		t = 8.3 ms
I <sup>2</sup> √t	1450	A <sup>2</sup> √s	t = 0.1 to 10 ms, V <sub>RRM</sub> = 0 following surge.
V <sub>FM</sub>	1.0	V	I <sub>F(AV)</sub> = 3A (9.4A peak); T <sub>J</sub> = 25°C.
I <sub>R(AV)</sub>	0.3	mA	Max. rated I <sub>F(AV)</sub> , V <sub>RRM</sub> and T <sub>L</sub> = 100°C. (ℓ = 9.5 mm (0.375 in.))

① I<sup>2</sup><sub>t</sub> for time t<sub>x</sub> = I<sup>2</sup>√t · √t<sub>x</sub>.

## THERMAL-MECHANICAL SPECIFICATIONS

T <sub>J</sub>	Max. operating junction temperature range	-65 to 175	°C
T <sub>stg</sub>	Max. storage temperature range	-65 to 175	°C
R <sub>thJC</sub>	Max. internal thermal resistance, junction-to-lead	16.5	deg. C/W
wt	Approximate weight	0.65 (0.023)	g (oz.)

## 3 AMP MEDIUM POWER SILICON RECTIFIER DIODES



Cathode Indicated by Color Band  
All Dimensions in Inches (Millimeters).

## MECHANICAL CHARACTERISTICS

CASE: Molded plastic use Flame Retardant Epoxy.

TERMINALS: Axial leads, solderable per MIL-STD-202, Method 208.

POLARITY: Color band denotes cathode.

MOUNTING POSITION: Any.

# 30S Series

## RATING AND CHARACTERISTIC CURVES




Fig. 1 - Average Forward Current Vs. Lead Temperature at Heat Sinks,  $l = 9.5$  mm (3/8 Inch) (Single Phase Operation)




Fig. 2 - Maximum Forward Voltage Vs. Forward Current




Fig. 3 - Maximum Forward Power Loss Vs. Forward Current (Sinusoidal Current Waveform)




Fig. 4 - Maximum Transient Thermal Impedance, Junction-to-Lead, Vs. Pulse Duration




Fig. 5 - Maximum Non-Repetitive Surge Current Vs. Number of Current Pulses

This datasheet has been download from:

[www.datasheetcatalog.com](http://www.datasheetcatalog.com)

Datasheets for electronics components.